



STRONG SRT 4651X

- **Component Video Outputs**
- **Advanced Blind Scan**
- **USB 2.0 Interface**
- **Super Sensitive Tuner**

- **10,000 Programmable Channels**
- **DVB, MPEG-2 Compliant**
- **DiSEqC 1.2 and USALS Compatible**
- **Downloadable Software Upgrades**
- **Data Transfer Between Units**
- **Teletext**
- **Electronic Program Guide**
- **Parental Lock**
- **16 Favorite Channels Groups**
- **Channel Sorting by Alphabet, Transponder or CAS**
- **OSD in 10 Languages**
- **Games with Stereo Sound**
- **Component: Y / Pb / Pr Video Outputs**
- **Coaxial S/PDIF Digital Audio Output**
- **Multi Picture Display and Zoom**
- **Colour Control**
- **Virtual Calculator**
- **Auto Voltage (AC 90~250V) SMPS**

DIGITAL SATELLITE RECEIVER



STRONG

www.strong-technologies.com

not just by name



IF SECTION

Input Frequency Range	: 950 - 2150 MHz	I.F. Bandwidth	: 36 MHz						
Input Frequency Level	: -85 dBm ~ -25 dBm	Input Return Loss	: -6 dBm						
Noise Figure	: 10 dB Max.	Tuning Step Size	: 125 KHz						
Input Impedance	: 75 ohm	Demodulation	: Shaped QPSK						
LO1 Phase Noise:	<table border="1"> <tr> <th>Offset Freq.</th> <th>dBc/Hz</th> </tr> <tr> <td>10 KHz</td> <td>-75</td> </tr> <tr> <td>100 KHz</td> <td>-95</td> </tr> </table>	Offset Freq.	dBc/Hz	10 KHz	-75	100 KHz	-95	Symbol Rate	: 2-45 Mbauds
Offset Freq.	dBc/Hz								
10 KHz	-75								
100 KHz	-95								
		FEC Coding	: Concatenated Viterbi & Reed-Solomon						
		Viterbi Rates	: k=7 Rate 1/2, 2/3, 3/4, 5/6, 7/8, AUTO						
		Roll-off Factor	: 35%						
Acquisition Frequency Uncertainty	: Auto								
Eb No Performance, BER	: Exceeds DVB Recommendation for all FEC Rates								

LNB SECTION

Connector	: F-Type - Loop-through	Band (Hi/Lo) Selection	: 22 KHz On/Off
Power	: 400 mA Max.	DiSEqC 1.2	: 64 Universal LNB Control
Polarization	: Horizontal : DC 16-19 V Vertical : DC 12-14.5 V	USALS	: Positioner Control Automatic Satellite Locator

SYSTEM RESOURCES

Processor	: 32 bit (150 MHz)	FLASH	: 2 Mbyte
SDRAM	: 16 Mbyte	EEPROM	: 32 Kbit

VIDEO SECTION

Decoding	: MPEG-2 & MPEG-1 Compatible	Bar Amplitude Error	: 6%
Compression Technique	: Main Profile, Main level	Field Time Distortion	: 3% Max.
Format	: PAL, NTSC	Line Time Distortion	: 3% Max.
Frame Rate	: 25 Hz, 30 Hz	Short Time Distortion	: 5% Max.
Aspect Ratio	: 4:3, 16:9	Luminance Nonlinearity	: 5% Max.
Active Pixel	: 720 x 576, 720 x 480	Differential Gain	: 5% Max.
Output Impedance	: 75 ohm	Differential Phase	: 5° Max.
Composite Output Level	: 1Vp-p±0.1Vp-p (75 ohm load)	S/N Unweighted	: 56 dB Min.
Component Output Level	Y : 1Vp-p±0.1Vp-p (75 ohm load) Pb : 0.52 Vp-p 0.05Vp-p (75 ohm load) Pr : 0.52 Vp-p 0.05Vp-p (75 ohm load)	C/L Intermodulation	: 5% Max.
		Chrominance Nonlinearity	: 5% Max.
		C/L Delay	: 75 nsec Max.
Data Rate	: Up to 15 Mb/s	Frequency Response	: 3 dB Max. (0.5-5.0 MHz)

AUDIO SECTION

Compression Technique	: MPEG-1, 2 Layer 1 & 2	Output Level	: 3.0 Vp-p Max.
Sound Mode	: Dual (Main/Sub), Stereo	Output Impedance	: 600 ohm
Sampling Frequency	: 32 KHz, 44.1 KHz, 48 KHz	Total Harmonic Distortion	: 0.3% Max. at 1 KHz
Frequency Response	: 2.0 dB - 15 Hz to 20 KHz		

CONNECTORS SECTION

Component Y / Pb / Pr	: RCA x 3	Aerial In	: IEC Female
A/V Out	: RCA x 3	Service Port	: RS-232C (115 Kbps Max.)
RF Out	: IEC Male	Digital Audio Output	: RCA
USB 2.0	: Type A Port		

MODULATOR SECTION

Output	: PAL G/I/K	CH	: 21-69 UHF (PLL Controlled)
--------	-------------	----	------------------------------

POWER SUPPLY

AC 90-250 V, 50-60 Hz, 25 W Max.	Power Consumption	: 25 W Max. (Operating Mode)
----------------------------------	-------------------	------------------------------

PHYSICAL SPECIFICATIONS

Size (W x H x D)	: 260 x 58 x 240mm	Net Weight	: 1.9 Kg.	E. & O. E.
------------------	--------------------	------------	-----------	------------

DISTRIBUTED BY:



STRONG TECHNOLOGIES PTY LTD. - 60 WEDGEWOOD ROAD, HALLAM, VICTORIA 3803, AUSTRALIA
 PH: +61 3 8795-7990 FAX: +61 3 8795-7991

TECHNICAL SUPPORT: 1 800 820 030

STRONG & CO. (FAR EAST), LTD. - P. O. BOX 85, YOKOHAMA, KANAGAWA-KEN, JAPAN 231-91 - FAX: +81 45 651-1842

www.strong-technologies.com

E-mail: asales@strong-technologies.com